

Product Name: Cutback Bitumen RC-70

HS Code: 27150000

<u>Property</u>	Typical Value	<u>Test</u> <u>Method</u>	Specification / Limit	<u>Result</u>
Kinematic Viscosity @ 60°C (cSt)	<u>70</u>	ASTM D2170	60 - 80	72
Flash Point (°C, Tag Closed Cup)	38 Min	<u>ASTM</u> <u>D56</u>	≥ 38	42
Distillation Test – Distillate to 225°C (% by volume)	40	ASTM D402	<u>35 – 45</u>	41
Distillation Test – Distillate to 360°C (% by volume)	<u>65</u>	ASTM D402	60 - 70	66
Residue from Distillation to 360°C (%)	<u>60</u>	ASTM D402	≥ 55	<u>61</u>
Penetration of Residue @ 25°C (0.1 mm)	100	ASTM D5	<u>85 - 115</u>	102
Ductility of Residue @ 25°C (cm)	<u>95</u>	ASTM D113	<u>≥ 75</u>	<u>97</u>





Solubility in CS2 (%)	99.0 Min	ASTM D4	≥ 99.0	99.5
Water Content (%)	0.2 Max	ASTM D95	≤ 0.2	0.04
<u>Appearance</u>	Dark brown to black, viscous liquid	<u>Visual</u>	Dark brown to black, viscous liquid	Dark brown to black, viscous liquid